

EMW – Stützwinkel / Ecken und Rabatten

- 12 cm Wandstärke
- Beidseitig schalungsglatt
- Betongüte C35 / C45
- Lastfall 1 bis 5 KN/m² und Lastfall 2 bis 33 KN/m²
- Qualitätsnachweis über Zertifizierung

Stand 2024

Maße H / L / Fuß (cm)	Lastfall (KN/m ²)	Gewicht (kg)	VE Stück/Palette
L – Steine			
55 x 99 x 30	2-33	ca. 225	4
55 x 49 x 30	2-33	ca. 110	8
80 x 99 x 45	2-33	ca. 340	4
80 x 49 x 45	2-33	ca. 165	6
105 x 99 x 60	2-33	ca. 465	3
105 x 49 x 60	2-33	ca. 230	6
130 x 99 x 70	2-33	ca. 565	2
130 x 99 x 70	1-5	ca. 565	2
130 x 49 x 70	2-33	ca. 280	4
155 x 99 x 85	2-33	ca. 830	2
155 x 99 x 85	1-5	ca. 830	2
155 x 49 x 85	2-33	ca. 410	2
180 x 99 x 100	2-33	ca. 970	1
180 x 99 x 100	1-5	ca. 970	1
180 x 49 x 100	2-33	ca. 480	1
Stützwinkel Ecken einteilig 90 Grad			
55 x 49 x 49 x 30	2-33	ca. 180	4
80 x 49 x 49 x 45	2-33	ca. 260	4
105 x 99 x 99 x 60	2-33	ca. 750	1
130 x 99 x 99 x 70	2-33	ca. 900	1
Rabattensteine			
30 x 99 x 12	2-33	ca. 90	9

